

Overview

These vacuum cleaners are suitable to pick up dust and small deposits. It is not suitable for liquid suction. They are sturdy and powerful, simple to use with its tool kit. It is suitable for collective use, for example: hotels, schools, hospitals, factories, offices, shops etc. The equipment is HIGH HAZARD. They are used to separate all dust with all limit values of occupational exposure including carcinogenic and pathogenic.

TECHNICAL DATA	GS 2/62 H 240V	GS 2/62 H 110V
Usage	Dry	
Motor	2	
Power	2000-2400W max	
Voltage	220-240V	110-115V
Water Lift	2470mmH ₂ O	
Airflow	420m ³ /h	
Tank Capacity/Material	62l / Steel	
Cable Length	8,5m	
Filtering Surface	12,000cm ²	
Sound Pressure Level	74dB[A]	
Diameter of Accessories	38mm	36mm
Dimensions (LxWxH)	550x600x960mm	
Weight	21,0kg	

Most Frequently Used

PHARMA INDUSTRY

AGRICULTURE

CONSTRUCTION

INDUSTRY

LOGISTIC & TRANSPORT



Exclusive Features

- ▶ STRONG HOOKS
- ▶ MICROFIBER BAG
- ▶ H CLASS CERTIFIED
- ▶ INNOVATIVE GASKET
- ▶ HEPA H14 CARTRIDGE
- ▶ MULTISTAGE FILTRATION
- ▶ SCREWING CONNECTION
- ▶ SAFETY DISPOSAL SYSTEMS
- ▶ FILTER OVER PRESSURE INDICATORS
- ▶ RESISTANT FRAMEWORK AND INLET PLUG
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ INDEPENDENT MOTORS

POWER MAX

2400 / 2000
W

WATER LIFT

2470 / 2560
mmH₂O

AIRFLOW

420
m³/h

TANK CAPACITY

62
l